

LDJ-5MD/LDJ-5M

Oil Centrifuge

This machine can be applied to test the contents of water and other sediments in the oil or the insoluble ingredients in the lubricant.



1 Technical performance

- It has micro-computer control, electronic lock and AC variable-conversion motor which delivers high torque.
- Digital LCD screen make visualized operation conveniently.
- It has self-locking, over-speed detection, over-temperature detection, imbalance detection that is automatic alarm device.
- Essential configuration included rotor exchange, speed/RCF, time, temperature, 9 levels acceleration and deceleration is the most economical choice.
- Silastic sealed ring conform to GMP, US FDA certificated.

2 Specification





Model	LDJ-5MD	LDJ-5M
Max speed	4000r/min	5000r/min
Max RCF	4690xg	3850xg
Max capacity	4x100ml/200ml	36x10ml
Speed accuracy	± 10r/min	
Time setting	1s~99h59min59s	
Temperature setting	20~80°C	
Temperature accuracy	± 2°C	
Noise	<65dB(A)	
Power supply	AC220V 50Hz 20A	AC220V 50Hz 20A, 1.5kW
Consumption	2.5kW	1.5kW
Dimension (L×W×H)	715mm×460mm×1000mm	650mm×310mm×1100mm
Packing size(L×W×H)	880mm×360mm×1480mm/740mm×830mm×1300mm	
Net weight (No rotor)	320kg / 140kg	

3 Rotor



<195mm Length of Oil tube or large capacity used in LDJ-5MD

>195mm Length of Oil tube or small capacity used in LDJ-5MD



Oil Test Bottle