


VERTICAL LAMINAR FLOW CABINET

REF: BBS-V1300



LCD Display

Airflow velocity, UV timer, UV work time, system work time, real time.



UV Lamp

Emission of 253.7 nanometers for most efficient decontamination




Waterproof Socket

2 waterproof sockets are located in the side panel, for optimum convenience of using small devices inside the cabinet



GasTap



Side Glass Window

The transparent side glass windows maximize light and visibility inside the cabinet, providing a bright and open working environment.

VERTICAL LAMINAR FLOW CABINET

REF: BBS-V1300

Technical specifications

Parameters	Description
External Size (W*D*H)	1300*820*2040mm
Internal Size (W*D*H)	1200*645*610mm
Work Surface Height	750mm
Display	LCD Display
Airflow Velocity	Average of 0.3-0.5m/s
Material	Main Body: Cold-rolled steel with anti-bacteria powder coating
	Work Table: 304 stainless steel
	Side and Front Window: 5mm toughened glass, anti-UV
Pre-Filter	Polyester fiber, washable
HEPA Filter	99.999% efficiency at 0.3µm
Noise	<65dB
Front Window	Motorized
Max Opening	430mm
LED Lamp	12W*1
UV Lamp	30W*1
	Emission of 253.7 nanometers
Consumption	400W
Waterproof Socket	Two, total load ≤500W
Caster	Universal caster with leveling feet
Power Supply	AC220V±10%, 50/60Hz; 110V ± 10%, 60Hz
Standard Accessory	LED lamp, UV lamp*2, Base stand, Gas Tap, Waterproof socket*2
	Water tap(only for BBS-H1800)
Optional Accessory	Electric height adjustable base stand
Gross Weight	254kg
Package Size(W*D*H)	1450*1060*1650mm